

## RRS 0220 RECTIFIER



### TECHNICAL SPECIFICATIONS

Input Voltage	195VAC - 265VAC
Output Voltage	14.4VDC - 14.8VDC
Input Frequency	50 - 60Hz.
Output Current	20A max.
Regulation Tolerance	± %1
Lens Color	-
Ripple	≤ 100 mVpp
Efficiency (%)	≥ %85
Cooling Type	-
Special Features	Durable outer body resistant to environmental conditions, automatic cut-off system when charging is complete
Protection Class	IP20
Cable Length	-
Mounting Type	Easy removable connector structure
Length	217mm
Width	112mm
Height	67mm
Weight	950g
Protection	Overheating, Short Circuit, Overload, AC Fuse
Approvals / Certificates	ECE R10, TS EN 60335-2-29
Operating Temperature	-20 °C ~ +60 °C
Warranty Period	2 yıl
Applications	Police, Gendarmerie, Ambulance, Firefighting, Airport, Municipality, Highways, Private Service, Official Vehicles, Tow Truck, Caravan

### ADVANTAGES

- Durable outer body resistant to environmental conditions
- Fast installation with easy removable connector structure
- Automatic safety system that cuts off charging when battery charging is complete
- Overheating, short circuit and overload protection features
- Compliance with ECE R10 and TS EN 60335-2-29 standards
- Wide area of use: Police, ambulance, airport, municipality, tow vehicles and more
- Compact dimensions and lightweight structure (1050 gr)
- 2-year warranty period

