



## MVL 0601 V LAMP



### TECHNICAL SPECIFICATIONS

Operating Voltage	10VDC - 30VDC
Nominal Voltage	12VDC / 24VDC
Current Consumption	0.6 - 1.5A
Dome Color	
LED Color	
Lens Color	Clear, colorless
Flash Frequency	1 - 20Hz.
Number of Flash Patterns	Multiple flash patterns synchronized with ZER products
Synchronization	Compatible synchronization with ZER products
Special Features	UV-resistant polycarbonate housing, ergonomic V-shaped design
Interface	Control via ZER products
Cable Length	1m
Mounting Type	Optional mounting compatible with all vehicle types
Length	230mm
Width	82mm
Height	55mm
Weight	344gr
Protection Rating	IP65
Approvals / Certifications	ECE R10, IP65
LED Lifetime	50,000 hours
Operating Temperature	-40 °C ~ 65 °C
Warranty Period	2 years
Applications	Police, Gendarmerie, Ambulance, Fire Brigade, Airport, Municipality, Highways, Special Service Vehicles, Tow Trucks

### ADVANTAGES

- UV-resistant polycarbonate outer housing suitable for harsh environments
- Exceptional brightness and visibility with high-power LEDs and Fresnel lens
- Multi-purpose ergonomic V-shaped design
- Synchronizable flash patterns with ZER products
- Low current consumption protects battery life
- Optional mounting compatible with all vehicle types
- Wide color options: Blue, Red, Amber, Green, White
- Compliance with IP65 standards
- Long LED lifetime of 50,000 hours
- Lightweight design
- 2-year warranty

