



PENTAGON LAMP



TECHNICAL SPECIFICATIONS

Operating Voltage	10VDC - 30VDC
Nominal Voltage	12VDC / 24VDC
Current Consumption	0.3 - 1.2A
Dome Color	
LED Color	
Lens Color	Clear, colorless
Flash Frequency	1 - 20Hz.
Number of Flash Patterns	Multiple flash patterns synchronizable with ZER products
Synchronization	Compatible synchronization with ZER products
Special Features	360° rotatable, vibration-resistant special mounting mechanism
Interface	Controlled via ZER Siren Unit
Cable Length	100mm
Mounting Type	360° dönebilen, özel mekanizmalı sabitleme
Length	120mm
Width	94mm
Height	44mm
Weight	410gr
Protection Rating	IP65
Approvals / Certifications	ECE R10, ECE R65, IP65
LED Lifetime	50,000 hours
Operating Temperature	-40 °C ~ 65 °C
Warranty Period	2 years
Applications	Police, Motorcycle, ATV, Airports and Special Service Vehicles

ADVANTAGES

- Polycarbonate outer housing resistant to UV rays and harsh environmental conditions
- High visibility and brightness with high-power LEDs and special Fresnel lens design
- System integrity through multiple flash patterns synchronizable with ZER products
- Low current consumption extends battery life
- Flexible mounting on any surface with a 360° rotatable, vibration-resistant special mounting mechanism
- Powerful light performance with 3W high-power LEDs
- Reliable operation in all climates with operating temperature range of -40°C to +65°C
- Maintenance-free long-term use with 50,000-hour nominal LED lifetime
- Lightweight design (410 g) for easy installation and portability
- Suitable for a wide range of applications including Police, Motorcycles, ATVs, Airports and Special Service Vehicles
- 5 color options: Blue, Red, Amber, Green, White
- Compliant with international standards: IP65, ECE R10 and ECE R65
- Safe and supported use with 2-year warranty

