


34 CM LINEAR LAMP



TECHNICAL SPECIFICATIONS

Operating Voltage	10VDC - 30VDC
Nominal Voltage	12VDC / 24VDC
Current Consumption	1.8 - 4.2A
Dome Color	Black
LED Color	
Lens Color	Clear, colorless
Flash Frequency	1 - 20Hz.
Number of Flash Patterns	16
Synchronization	Supports synchronized operation with ZER systems
Special Features	Waterproof structure, modular structure, easy installation with adjustable feet, Form-fitting custom PCB; LED / LED-LED Driver / LED-LED Driver-Entegre.
Interface	On/off and mode control via button on vehicle cigarette lighter
Cable Length	4 m waterproof connector cable
Mounting Type	Quick adaptation to all vehicle types and in-vehicle / external use with modular parts and mounting brackets
Length	Variable depending on the number of modules
Width	34cm
Height	5.3cm
Weight	-
Protection Rating	IP65
Approvals / Certifications	ECE R10, IP65
LED Lifetime	50,000 hours
Operating Temperature	-40°C ~ 65°C
Warranty Period	2 years
Applications	Police, Gendarmerie, Ambulance, Fire Department, Airports, Municipality, Highways, Special Service, Official Vehicles, Tow Trucks

ADVANTAGES

- Full compatibility with all vehicle systems with 12–24 VDC operating voltage
- Maximum light performance and visibility with high-efficiency, specially designed optical lens
- Protects battery life and provides energy efficiency thanks to low power consumption
- Safe and long-lasting use in outdoor conditions with waterproof structure
- Impact resistance with an aluminum outer housing durable to environmental conditions
- Suitable for various warning scenarios thanks to 16 stored flash modes
- Customization for different vehicles and applications with modular structure (2–6 modules)
- 6 pcs 3W power LEDs per module, total high light capacity up to 12–36 LEDs
- LED, LED-LED Driver, and LED-LED Driver-Integrated. Low current consumption protects battery
- Easy and safe connection with 4 m waterproof connector cable
- Provides IP sealing with waterproof connector entry
- Easy mounting to the right and left sides thanks to adjustable mounting feet
- Wide range of applications: Police, Gendarmerie, Ambulance, Fire Brigade, Municipality, Airport, Highways and private service vehicles
- 5 different color options: Blue, Red, Amber, Green, White
- Complies with international standards with ECE R10 certified structure
- Durable in all climate conditions with -40°C to +65°C operating temperature range
- Maintenance-free long-term performance with 50,000-hour LED lifetime
- Reliable and supported product use with 2-year warranty

