



WCL 0792 WARNING LIGHT CYLINDRICAL BIG SIZE CENTER MOUNT



TECHNICAL SPECIFICATIONS

Operating Voltage	10VDC - 30VDC
Nominal Voltage	12VDC / 24VDC
Current Consumption	0- 3A
Dome Color	
LED Color	
Lens Color	Specially designed Fresnel lens providing 360° visibility
Flash Frequency	1 - 20Hz.
Number of Flash Patterns	Multiple flash modes capable of synchronized operation with ZER products
Synchronization	Synchronization feature compatible with ZER products
Special Features	UV resistance, 360° visibility, high brightness, operation via cigarette lighter, optional roof mounting with N35 neodymium magnet
Interface	Control by connecting to vehicle cigarette lighter
Cable Length	100mm
Mounting Type	Permanent mounting with internal screw
Length	190mm
Width	190mm
Height	200mm
Weight	1065gr
Protection Rating	IP65
Approvals / Certifications	ECE R10, ECE R65, IP65
LED Lifetime	50,000 hours
Operating Temperature	-40°C ~ 65°C
Warranty Period	2 years
Applications	Ideally suited for larger vehicles requiring central mounting.

ADVANTAGES

- Polycarbonate outer housing resistant to UV rays and harsh weather conditions
- Exceptional brightness and visibility with specially designed Fresnel lens providing 360° visibility
- Full synchronization support with ZER products
- Low current consumption helps protect battery life
- Control by connecting to vehicle cigarette lighter
- Secure roof mounting with optional high-strength N35 grade neodymium magnet
- Powerful light performance with 36 high-power LEDs
- Compliance with ECE R10 and ECE R65, IP65 international certifications
- Wide color options: Red, Blue, Amber, Green, White
- Very wide range of applications: Ideal for Police, Gendarmerie, Ambulance, Fire Department, Municipal and Special Vehicles
- Safe and long-lasting use with a 2-year warranty period

