

LRW 0311 LED WARNING LAMP (RECHARGEABLE)



TECHNICAL SPECIFICATIONS

Operating Voltage	6VDC
Nominal Voltage	6VDC
Current Consumption	Low power consumption
Dome Color	Amber
LED Color	Amber
Lens Color	Fresnel lens providing exceptional brightness with high-power LEDs
Flash Frequency	1 - 20Hz.
Number of Flash Patterns	2 (Night / Day modes)
Synchronization	Synchronized operation with ZER LED warning lamps
Special Features	360° rotating and bidirectional light structure, battery and charge status LED indicator
Interface	Cigarette lighter input or charging adapter connection
Cable Length	
Mounting Type	
Length	190mm
Width	100mm
Height	370mm
Weight	3550gr
Protection Rating	IP65
Approvals / Certifications	ECE R10, ECE R65, IP65
LED Lifetime	50,000 hours
Operating Temperature	-40°C ~ 65°C
Warranty Period	2 Years
Applications	Police, Gendarmerie, Fire Brigade, Airport, Municipality, Highway

ADVANTAGES

- Polycarbonate outer housing resistant to environmental conditions and UV exposure
- High visibility with specially designed Fresnel lens
- 360° rotating structure with dual-direction light output
- Different energy consumption modes for day and night operation
- Option for single-use or rechargeable batteries
- Colored LED indicators for battery status
- Rechargeable via vehicle cigarette lighter socket
- Up to 36 hours of continuous operation in daytime mode with a single battery
- Low power consumption to extend battery life
- Compliance with ECE R10, ECE R65, and IP65 standards
- Concrete-weighted base to prevent tipping or movement caused by external factors
- Wide range of applications and 2-year warranty

