

WRL 0919 SIDE LAMP



TECHNICAL SPECIFICATIONS

Operating Voltage	10VDC - 30VDC
Nominal Voltage	12VDC / 24VDC
Current Consumption	0.3 - 0.7A
Dome Color	
LED Color	
Lens Color	Clear, colorless
Flash Frequency	1 - 20Hz.
Number of Flash Patterns	Multiple synchronized flash patterns with ZER products
Synchronization	Compatible with ZER products
Special Features	UV-resistant polycarbonate housing, Form-fitting custom PCB; LED / LED-LED Driver / LED-LED Driver-Entegre.
Interface	Control via ZER products
Cable Length	100mm
Mounting Type	Body mounting
Length	230mm
Width	173mm
Height	65mm
Weight	457gr
Protection Rating	IP65
Approvals / Certifications	ECE R65, IP65
LED Lifetime	50,000 hours
Operating Temperature	-40 °C ~ 65 °C
Warranty Period	2 years
Applications	Ambulance, Fire Brigade, Airport, Service Vehicles, Tow Trucks

ADVANTAGES

- UV-resistant polycarbonate housing for harsh environments
- Exceptional brightness with high-power LEDs and Fresnel lens
- Synchronizable flash patterns with ZER products
- 18 different flash patterns
- The form-fitting custom PCB architecture is offered in three electronic configurations:
 - LED, LED-LED Driver, and LED-LED Driver-Integrated. Low current consumption protects battery
- Each LED rated at 3W, total of 18 LEDs for high illumination
- Suitable for fire trucks, ambulances, airport and tow vehicles
- Five color options available
- IP65, ECE R65 certified
- Long LED lifetime of 50,000 hours
- 2-year warranty

