



WCL 0792 WARNING LIGHT CYLINDRICAL SMALL SIZE CENTER MOUNT



TECHNICAL SPECIFICATIONS

Operating Voltage	10VDC - 30VDC
Nominal Voltage	12VDC / 24VDC
Current Consumption	0- 1A
Dome Color	
LED Color	
Lens Color	Specially designed Fresnel lens providing 360° visibility
Flash Frequency	1 - 20Hz.
Number of Flash Patterns	Multiple flash modes capable of synchronized operation with ZER products
Synchronization	Synchronization feature compatible with ZER products
Special Features	UV resistance, 360° visibility, high brightness, operation via cigarette lighter, optional roof mounting with N35 neodymium magnet
Interface	Control by connecting to vehicle cigarette lighter
Cable Length	100mm
Mounting Type	Attaching to motorcycle body with internal screw and optional mounting bracket
Length	Adjustable Height: Min: 50 cm, Max: 76 cm
Width	62mm
Height	790mm
Weight	630gr
Protection Rating	IP65
Approvals / Certifications	ECE R10, ECE R65, IP65
LED Lifetime	50,000 hours
Operating Temperature	-40°C ~ 65°C
Warranty Period	2 years
Applications	Police, Gendarmerie, Ambulance, Fire Brigade, Airport, Municipality, Highways, Private Service, Official Vehicles, Motorcycles, Tow Trucks

ADVANTAGES

- Polycarbonate outer body resistant to environmental conditions and UV rays
- Specially designed Fresnel lens providing 360° extraordinary brightness and visibility with high power Power LEDs
- Various flash patterns synchronized with ZER products
- Protecting battery life with low current consumption
- Possibility of permanent mounting with internal screw and attaching to motorcycle body with optional mounting bracket
- Suitability for different vehicle structures thanks to adjustable height
- Wide color option (Blue, Red, Amber, Green, White)
- Compliance with ECE R10 and ECE R65 standards
- 50,000 hours long LED life
- 2 years warranty period
- Lightweight and compact structure (630 gr)

