

FIXED PROJECTOR



TECHNICAL SPECIFICATIONS

| | |
|----------------------------|------------------------------------------------------------------------------------------------|
| Operating Voltage | 90-265V |
| Nominal Voltage | 90-265V |
| Current Consumption | |
| Dome Color | |
| LED Color | White |
| Lens Color | Transparent |
| Flash Frequency | Fixed |
| Number of Flash Patterns | Fixed |
| Synchronization | |
| Special Features | |
| Interface | |
| Cable Length | 40cm |
| Mounting Type | Fixed base mounting |
| Length | |
| Width | |
| Height | |
| Weight | 360gr |
| Protection Rating | IP65 |
| Approvals / Certifications | |
| LED Lifetime | 50,000 hours |
| Operating Temperature | -40 °C ~ 65 °C |
| Warranty Period | 2 years |
| Applications | Suitable for armored vehicles, tanks, and external vehicle-mounted warning/protection purposes |

ADVANTAGES

- Designed to protect lighting units from external impacts while allowing easy angle adjustment
- Patented by ZER Elektronik Sanayi ve Ticaret Ltd. Şti.
- Materials & Manufacturing: Stainless steel, galvanized steel, laser cutting, bending
- Plate Thickness: 2mm
- Suitable for armored vehicles, tanks, and external vehicle-mounted warning/protection purposes
- Warranty Period: 2 years

