



C TYPE MINI SPEAKER LIGHTBAR



TECHNICAL SPECIFICATIONS

| | |
|----------------------------|---|
| Operating Voltage | 10VDC - 30VDC |
| Nominal Voltage | 12VDC / 24VDC |
| Current Consumption | 1.2 - 2.2A |
| Dome Color |  |
| LED Color |  |
| Lens Color | Optical polycarbonate lens resistant to UV and harsh conditions |
| Flash Frequency | 1 - 20Hz. |
| Number of Flash Patterns | Multiple flash patterns that can operate synchronized with ZER products |
| Synchronization | Compatible synchronization feature with ZER products |
| Special Features | Robust stainless steel structure resistant to high speed and environmental conditions |
| Interface | On/off and mode control via button located on vehicle cigarette lighter or control via siren system and remote controller |
| Cable Length | 4m |
| Mounting Type | Optional mounting with N35 Neodymium Magnet |
| Length | 290mm |
| Width | 220mm/ 290mm |
| Height | 80mm |
| Weight | 7kg |
| Protection Rating | IP65 |
| Approvals / Certifications | SAE J1318, SAE J1849, SAE J1595, IP65 |
| LED Lifetime | 50,000 hours |
| Operating Temperature | -40 °C ~ 65 °C |
| Warranty Period | 2 years |
| Applications | Police, Gendarmerie, Ambulance, Fire Department, Airports, Municipality, Highways, Special Service, Official Vehicles, Tow Trucks |

ADVANTAGES

- Robust stainless steel body resistant to high speed and harsh environmental conditions
- Optical polycarbonate lens resistant to UV rays and severe conditions
- High brightness and visibility with high-power Power LEDs
- LED groups on both sides controlled by a single circuit
- Low current consumption to protect battery life
- Direct power supply via vehicle cigarette lighter socket
- Fast and secure installation with N35 Neodymium Magnet mounting
- Wide color options: Red, Blue, Amber, Green, White
- Compliance with SAE J1318, J1849 and J1595 standards
- 2-year warranty period
- Wide operating temperature range of -40 °C ~ +65 °C

