

OUTDOOR WARNING SIREN SPEAKER



TECHNICAL SPECIFICATIONS

Operating Voltage	600VDC
Nominal Voltage	600V Line
Current Consumption	-
Rated Power	600W RMS
Sound Pressure Level	126±3(Db)
Impedance	4-8-16 ohm
Frequency Range	160Hz. - 7kHz.
Magnet Type	Neodymium Magnet
Connection Type	-
Special Features	Aluminum horn structure resistant to water, moisture, corrosion, dust, vibration and impact
Housing Color	Gray
Cable Length	
Mounting Type	Fixed Mounting
Length	480mm
Width	480mm
Height	500mm
Weight	
Protection Rating	IP65
Approvals / Certifications	SAE J1849, EVS1, EVS2, EVS3, IP65, Acoustic Performance Test
Operating Temperature	-40 °C ~ 65 °C
Warranty Period	2 years
Applications	Suitable for military and civilian applications. Can be used in emergency and disaster situations.

ADVANTAGES

- Robust corrosion-resistant structure designed for harsh environmental conditions
- Aluminum housing resistant to water, humidity, corrosion, dust, vibration and impact
- Specially designed for communication, intercom and electronic alarm-announcement systems
- Suitable for both military and civilian applications
- Reliable and uninterrupted operation in both land and marine environments
- Powerful long-distance sound transmission with minimal signal loss
- Compliant with military requirements and relevant standards
- Quick and flexible installation with mounting brackets for various applications
- Applications: Marine systems, land platforms and defense industry projects
- Warranty: 2 Years

